




Technical Data Sheet

		UniPak 192 x 129 mm 1200 ml	
		Logical no: 5630 Available lids: 2530 (standard for pots out of Wetteren)	
Volume			
Volume under lid:	1200,0 ml +/- ml	Volume brimful:	1350,0 ml +/- ml
Dimensions			
Shape:	Rectangular	Length bottom:	173,4 mm +/- 0,5 mm
Length top with std. lid:	191,5 mm +/- 0,5 mm	Width bottom:	110,5 mm +/- 0,5 mm
Length top without std. lid:	191,5 mm +/- 0,5 mm	Height without lid:	72 mm +/- 0,5 mm
Width top without std. lid:	128 mm +/- 0,5 mm	Height with std lid:	72,6 mm +/- 0,5 mm
Width top with std. lid:	128 mm +/- 0,5 mm		
Weight			
Weight container/pot:	40 g +/- 4 g		
Weight standard lid:	16,3 g +/- 1,6 g		
Performance			
Stackability - dynamic:	Max: 0 kg Max top load on bottom container at 23°	UN approval:	No
Stacking tests:	Special: The stacking tests have been performed with the standard raw material as stated above at 23° C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to determine the viability of stacking and transportation.		
Closure system		Handle	
Lid type options:	Standard	Handle available:	None
Closure type:	Snap-On		
Protective collar:	Yes		
Tamper Evidence type:	Tamper Evidence tab		
Decoration			
Decoration available:	IML	Decoration area offset:	mm without overlap
Packing			
On pallet 1200x800:	1944 pcs.	On pallet :	NA pcs.
Pieces per layer:	NA pcs.	Pieces per layer:	NA pcs.
Height incl. pallet:	1,15 m	Height incl. pallet:	NA m
Stackability, empty:	2 pallets high	Stackability, empty:	NA pallets high
Raw material			
Raw material options:	PP	Masterbatch colours:	Colours according to RPC Superfos standard selected pantone colours.
Hot filling:	85-95° C	Cold temperatures:	Freezing conditions require special resins available on request. The RPC Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures
Hot temperatures:	The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The RPC Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures		
Quality Specifications			
Approvals:	All RPC Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.		
Shelf life:	The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very		

Quality information:

low temperatures or very high temperatures over a long period.
Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery.

Specifications are subject to change without notice. Version 10.2

Latest revision : 04-09-2013