



## Technical Data Sheet



### UniPak 195 x 195 mm 5000 ml

**Logical no:** 5548  
**Available lids:** 2540 standard

#### Volume

**Volume under lid:** 5000,0 ml +/- ml      **Volume brimful:** ml +/- ml

#### Dimensions

<b>Shape:</b>	Square	<b>Length bottom:</b>	160 mm +/- mm
<b>Length top with std. lid:</b>	195 mm +/- mm	<b>Width bottom:</b>	160 mm +/- mm
<b>Length top without std. lid:</b>	195 mm +/- mm	<b>Height without lid:</b>	190 mm +/- mm
<b>Width top without std. lid:</b>	195 mm +/- mm	<b>Height with std lid:</b>	191 mm +/- mm
<b>Width top with std. lid:</b>	195 mm +/- mm		

#### Weight

**Weight container/pot:** 146 g +/- g  
**Weight standard lid:** 30 g +/- 3 g

#### Performance

**Stackability - dynamic:** Max: kg Max top load on bottom container **UN approval:** No  
 at 23°

**Stacking tests:** **Special:**  
 The stacking tests have been performed with the standard raw material as stated above at 23° C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to determine the viability of stacking and transportation.

#### Closure system

**Lid type options:** Standard lid  
**Closure type:** Snap-On  
**Protective collar:** Yes  
**Tamper Evidence type:** Tamper Evidence tab

#### Handle

**Handle available:** None

#### Decoration

**Decoration available:** None      **Decoration area offset:** mm without overlap

#### Packing

<b>On pallet 1200x800:</b>	1536 pcs.	<b>On pallet 800x1200:</b>	864 pcs.
<b>Pieces per layer:</b>	NA pcs.	<b>Pieces per layer:</b>	NA pcs.
<b>Height incl. pallet:</b>	1,97 m	<b>Height incl. pallet:</b>	NA m
<b>Stackability, empty:</b>	2 pallets high	<b>Stackability, empty:</b>	NA pallets high

#### Raw material

**Raw material options:** PP      **Masterbatch colours:** Colours according to RPC Superfos standard selected pantone colours.  
**Hot filling:** 85-95° C

**Hot temperatures:**  
 The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The RPC Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures

**Cold temperatures:**  
 Freezing conditions require special resins available on request. The RPC Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures

#### Quality Specifications

**Approvals:** All RPC Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.

**Shelf life:** The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very

**Quality information:**

low temperatures or very high temperatures over a long period.  
Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery.

*Specifications are subject to change without notice. Version 10.2*

*Latest revision : 29-09-2014*