

Storage

Packaging should be stored in a dry place and without direct sunlight.

Traceability

Papier-Mettler labels all palettes, rolls and packaging units. Additionally, the delivery notes contain the order number. All relevant data concerning the production are encoded in this order number. A detailed traceability of the raw material, production machine and personnel is provided. All production processes are reproducible. Traceability and documentation is ensured. Thus, Papier-Mettler meets all legislative requirements concerning traceability according to Regulation (EC) No 1935/2004, which became effective in 2006.

Migration

The overall migration limit is adhered to under the following testing conditions:

Simulant	Test duration	Test temperature
Deionized water	10 days	40 °C
acetic acid 3 Gew%	10 days	40 °C
ethanol 95 Vol%	10 days	40 °C
isooctane in exchange for fat	2 days	20-+1 °C

Testing for 10 days at 40 °C shall cover any long term storage at room temperature or below, including when packaged under hot-fill conditions, and/or heating up to a temperature T where $70\text{ °C} \leq T \leq 100\text{ °C}$ for a maximum of $t = 120/2^{(T-70)/10}$ minutes.

Papier-Mettler has access to information referring to substances that are subject to limitations and/or specifications and dual use additives from the pre-suppliers (of the PE window film) and can be shown to the above-mentioned company and authorities upon request.

Surface to volume ratio: 6 dm²/kg

A functional barrier made from plastic is not used in the above mentioned product.

PAPIER-METTLER KG
Paper and Plastic
Packaging

This letter has been created automatically and is valid without signature.